

Declaration of Compliance

Description	Material	Article Number
Cardboard boxes "VIKING" and corresponding lids	Cardboard/PLA	

Duni declares that the article meets the requirements of:

- Article 3, 11(5), 15 and 17 of Regulation (EC) No 1935/2004 (Framework regulation)
- EU Regulation 2023/2006/EC (GMP)
- LFGB §31 (German Food, Commodities and Feed Code), which implements the provisions of EU Regulation 1935/2004 into German law, and BfR Recommendation XXXVI
- EU Regulation 10/2011/EC with amendments (Plastic regulation)
- EU Regulation (EU) 2024/3190 on the use of bisphenol A (BPA) and other bisphenols
- Article 5 of Regulation (EU) 2025/40 on Packaging and Packaging Waste (PPWR) regarding the restriction of per- and polyfluoroalkyl substances (PFAS)

Overall migration

According to the above-mentioned regulations, the overall migration does not exceed 10 mg/dm² or 60 mg/kg.

Specific migration

The material contains monomers or additives subject to restrictions under the plastic regulation 10/2011 and its amendments. A specific migration test proves that these are within the limits. If more information regarding the monomers or additives is needed, please contact Duni Group.

Area of use

The boxes can be used for long-term storage of all kinds of foods except highly aqueous food, at room temperature or lower (provided the food remains safe to consume and maintains its desired quality). They are also suitable for hot-fill applications, allowing filling with food at 100°C.

Microwave use: The boxes can be used in a microwave oven, but make sure not to use higher power and longer duration than the box keeps its strength and stability during use. Heating directly from the freezer is not recommended.

Freezing: The boxes can be used for frozen food. The boxes are also safe to use for storage in the freezer but be aware thawing may impact the appearance and stability of the cardboard.

Food compatibility: Different kinds of food may have an impact on the physical behavior of the paperboard. Duni recommend the customer to test their specific application to ensure it meets their requirements.

Test conditions

Migration tests on the material of the article performed by an independent institute showed that under the following test conditions overall migration (see 1.) and specific migration (see 2.) fall below the respective limits given by regulation 10/2011.

Overall migration OM2

Simulant	Contact time	Temperature	Result (mg/dm ²)
10 % Ethanol	10 days	40°C	< 10
3% Acetic acid	10 days	40°C	< 10
95 % Ethanol	10 days	40°C	< 10
Isooctane	2 days	20°C	< 10

Overall migration OM5

_____ -
_____ -

To the best of our knowledge, the information provided is accurate and reliable as of the date of publication and, where relevant, reflects the information received from suppliers. It is valid from the stated issue date until it is replaced or superseded.